DMS 1819 B¹₂, B¹₂K, B2, B2K, B2PF, B2PF

U.S. DEPARTMENT C LABOR
Occupational Safety and Health Administration

Form Approved OMB No. 44-R1387

MATERIAL SAFETY DATA SHEET

MAY 26 1982

Required under USDL Safety and Health Regulations for Ship Repairing,
Shipbuilding, and Shipbreaking (29 CFR 1915, 1916, 1917) 45 1819 B28F (20)

SECT	ION I
MANUFACTURER'S NAME Essex Chemical Corp.	EMERGENCY TELEPHONE NO. (213) 537-7600
ADDRESS (Number, Street, City, State, and ZIP Code) 19451 Susana Rd., Compton, CA 9022	21
CHEMICAL NAME AND SYNONYMS N/A	Pro-Seal 735/Accelerator
CHEMICAL FAMILY N/A	FORMULA N/A

SECTION	11 -	HAZAF	RDOUS INGREDIENTS		
PAINTS, PRESERVATIVES, & SOLVENTS	%	TLV (Units)	ALLOYS AND METALLIC COATINGS	%	TLV (Units)
PIGMENTS			BASE METAL		
CATALYST Lead peroxide 55-6	0%		ALLOYS		
VEHICLE			METALLIC COATINGS		
SOLVENTS			FILLER METAL PLUS COATING OR CORE FLUX		
ADDITIVES			OTHERS		
OTHERS	1 1		· · · · · · · · · · · · · · · · · · ·		
HAZARDOUS MIXTURES	OF (OTHER LIC	DUIDS, SOLIDS, OR GASES	%	TLV (Units)
	- -				
			:	ŀ	

SECTION III - PHYSICAL DATA					
BOILING POINT (°F.)	N/A	SPECIFIC GRAVITY (H2O=1)		2.2	
VAPOR PRESSURE (mm Hg.)	N/A	PERCENT, VOLATILE BY VOLUME (%)		0	
VAPOR DENSITY (AIR=1)	N/A	EVAPORATION RATE (=1)	:	N/A	
SOLUBILITY IN WATER	Nil				
APPEARANCE AND ODOR Brown	paste, sligh	t odor			

SECTION IV - FIRE	AND EXPLOSI	ON HAZARD DA	ΓΑ	
FLASH POINT (Method used)	FLAMMABLE LIMITS		Lel	Uel
Over 230°F		N/A		
EXTINGUISHING MEDIA				
Dry chemical, fo	am. CO. wa	ter		
SPECIAL FIRE FIGHTING PROCEDURES	<i>L</i>			
Wear c	annister fa	ce mask.		
	·			
UNUSUAL FIRE AND EXPLOSION HAZARDS None				
	- 1			
			<u> </u>	

	1	3	ECHON	A A	- HEA	LTH HAZ	ARD D	PATA
THRESHOLD LIMI	TVALU	e Unknown						
EFFECTS OF OVE	REXPOS	URE				t	ina	and headache.
		II INE	esteu	1-116	iusea	VOMIL.	Ing o	and neadache.
EMERGENCY AND	FIRST	AID PROCEDU	JRES ,					
						con	sult	physician
		·						

			SECTION	י אס	VI - R	EACTIVIT	Y DA	ГА
STABILITY	UNS.	TABLE		co	NOITION	IS TO AVOID		
	STA	STABLE X					· · · · · · · · · · · · · · · · · · ·	
INCOMPATABILIT	Y (Mater	ials to avoid)	Stro	ng	redu	cing ag	ents.	•
HAZARDOUS DEC	OMPOSI	TION PRODU	CTS Non					
	*	T				CONDITIO	NS TO A	AVOID
HAZARDOUS POLYMERIZATIOI	N	MAY OCCUI	₹			<u> </u>		
		WILL NOT	OCCUR		X			
		SECT	ION VI	1 -	SPILL	OR LEAK	PROC	EDURES
STEPS TO BE TAK	EN IN C	ASE MATERI	AL IS RE	LEAS	ED OR S	PILLED C1	ean s	spillage with rags or
sweeping								
	· · · · · · · · · · · · · · · · · · ·							
WASTE DISPOSAL	METHO	<u> </u>			. '			
		should be	in ac	CODO	dance i	with fed	eral,	state and local
regulation	S.							
						·		
		SECTION	VIII -	SPE	CIALP	ROTECTI	ON IN	FORMATION
RESPIRATORY PR	OTECTI	ON (Specify ty	vpe)			·		and the second s
VENTILATION	VENTUATION LOCAL EXHAUST					SPECIAL		
. :	MEC	HANICAL (Ge	neral)					OTHER
		- IAMEAL OC			······································	·		
	VES					EYE PROT	ECTION	afety goggles.
PROTECTIVE GLO	Neop	rene					ى د	arce) 6066±00.
	Neop	IPMENT	vera1	.1s	apr			1100 60882001
PROTECTIVE GLO	Neop	IPMENT	veral	ls,	, apr			aret, goggreet
	Neop	CO						

PAGE (2)

GPO 934-130

Store in closed container below 80°F.
OTHER PRECAUTIONS Yellow label material.

Form OSHA-20 Rev. May 72